

**KOMATSU**

# EX50

S E R I E S

**10 - 16 ton**

**Diesel Pneumatic-Tyre Trucks**

*EPA Tier 3/EU Stage IIIA Emission Compliant*



Komatsu Utility Tochigi Plant has been certified according to ISO 9001 Quality Management System and ISO 14001 Environmental Management System.

For other options and attachments, please consult with your Komatsu dealer. Features and specifications may vary in different countries and regions. Please contact your Komatsu dealer to confirm machine details in your region. Forklift trucks in this catalog may be shown with optional equipment. Komatsu products and specifications are subject to change without notice. The performance values indicated herein represent nominal values obtained under typical operating conditions.

**Komatsu Utility Co., Ltd. FORKLIFT COMPANY**

Head office 2-4-1, Shiba-koen, Minato-ku, Tokyo 105-0011, Japan  
URL: <http://www.komatsu-utility.com>  
Fax: +81-3-3433-3120



Form No. BR-EX50-003-ENG  
Printed in Japan 0308-1-05YIT

**KOMATSU FORKLIFT**

# Environment & Economy is the word for the next generation. EX50 Series is our answer for it.

Komatsu put its technologies and know-how into the design and construction of a new engine, which is a proof of our careful consideration of the next step. With its new cutting edge four key technologies, the new engine provides reliable power with better fuel efficiency for maximum productivity and lowered operating cost while being environment-friendly.



## Engine Technologies

Key Technology-1

**Electronic Control System**

Key Technology-2

**Heavy duty HPCR System**

Key Technology-3

**New Combustion System**

Key Technology-4

**Air to Air Charge Air Cooling System**

**10t/11.5t/13.5t/15t/16t**

**Diesel Pneumatic-Tyre Trucks**  
EPA Tier 3/EU Stage IIIA Emission Compliant

**EX50**  
S E R I E S



Born of the unsurpassed technologies  
Shaped from the deep thoughtfulness for environment.




## ENVIRONMENTAL SAFETY

The new engine adopts the latest technologies that supports both reliable power and environment-friendliness

EPA Tier 3/ Euro IIIA compliant SAA6D107E-1 engine adopts Komatsu's latest engine technologies, and dramatically reduces NOx and PM in exhaust. Also, each system successfully interacts for better fuel efficiency and lowered running noises. Reliable fuel filters keep systems performance high and protect components. The engine offer full performance and power even in severe conditions.

- Rated Output : **122kW @ 2,200rpm**
- Maximum Torque : **575Nm @ 1,600rpm**




HIGH POWER CLEAN DIESEL ENGINE  
**SAA6D107E-1**

### Key Technology-1: Electronic Control System

The center control unit quickly processes signals from various sensors on the vehicle in order to produce a maximum power in any condition, eliminating possible loss in engine performance.


### Key Technology-2: Heavy duty HPCR System

High pressure compressed fuel stored in an accumulator chamber, so-called common rail, is injected into each cylinder sufficiently at a proper timing by an ECU (Electric Controlled Unit). This HPCR (High Pressure Common Rail) system promises optimized fuel burning and reduced fuel consumption.



### Key Technology-3: New Combustion System


A unique shape of the combustion chamber on the top surface of each piston facilitates complete fuel burning by optimizing conditions, timings and amounts of fuel injection, which helps reduce NOx and PM in exhaust, as well as fuel consumption.



### Key Technology-4: Air to Air Charge Air Cooling System

This system cools high temperature air blown by the turbocharger and supplies it to cylinders.

As a result, the system maximizes combustion efficiency and emission performance, facilitating high output while reducing NOx and fuel consumption.




## SAFETY

**Wet disc brake that safely stop the vehicle in any working conditions (Option)**

The EX50 features Komatsu's original wet disc braking system that eliminates weakness of traditional drum brakes. With its built-in waterproof and dustproof mechanism, the braking system also delivers high durability with less brake shoe wearing. Because the braking system is enclosed, it does not require part replacement or overhauls for maintenance.\* Regardless of your working conditions, it offers added reliability and safety of the EX50.


\*Oil replacement and regular inspections are required.



**Operator Presence Sensing (OPS) system automatically stops traveling and lifting when the operator leaves the seat (Option)**

To avoid malfunctions and operations in the operator's unstable positions, the OPS system automatically prevents driving and loading when the operator is unseated. Indicators on the display panel inform the vehicle condition when it stops by the interlock. This mechanism conform with ISO3691-1, one of the worldwide safety standards.

\*This system is to safely stop the driving and loading function, and not intended to forcibly brake the vehicle.



### What about ISO3691-1

ISO3691 refers to a series of safety standards for industrial trucks to facilitate safe working.

**Good view, comfort seating and operability.  
All designed to deliver the higher level of workability.**



## MANEUVERABILITY

**Exceptionally high travel speed achieved through use of electrically controlled forward/reverse lever and 3-speed transmission (or optional automatic transmission)**

A best-of-breed combination of high-power new engine and powershift 3-speed transmission (or optional automatic transmission) with forward/reverse lever ensures excellent maneuverability and the optimum high-performance combination of travel speed, acceleration, lift speed, and gradability.

- **Traveling Speed** (at the third gear, unloaded) : **32km/h**
- **Gradability** (FD 100) : **38% (21 degrees)**


**Top-of-class rated lift speed ensures speedy and efficient work**

A top-of-class lift speed can be achieved in both loaded and unloaded states through optimization of the oil-level efficiency of the large-capacity tandem hydraulic pump (common to 10-ton to 16-ton models) as well as use of the new hydraulic circuit (load-sensing valve).


- **Lifting Speed** (Loaded/FD100) : **470mm/s**

## COMFORT

**Greatly enhanced front/rear visibility achieved by improved top of the counter weight shape and expanded inner width of the mast**



Improvement in the shape of the back portion of the rear weight enhances rearward visibility, which has been a blind spot for the operator. Moreover, arrangement of the chains outside of the mast allows the inner width of the mast to be expanded to 642 mm [25.3 inches] (FD100), ensure the good frontward visibility essential for safe operation.



- **Inner width of the mast** (FD100 2-stage view mast) : **642mm [25.3in]**

**Ambient - and operator-friendly low-noise design; complete sound - insulating measures**

- **During low idle** : **72dB (A)**

**New operator's suspension seat**

The new-design seat features a high-support structure that always balances and securely holds the operator's body, thus reducing fatigue during extended operation. It also provides retractable seat belt.



**Efficient design and functionalities for comfortable operations**

- 1 Integrated, easy-to-Read meter panel to ensure safe operation
- 2 Combination switch headlamp and directional Indicator (Auto-return)
- 3 Tilttable Steering wheel for operator comfort



## SERVICEABILITY

**Large-capacity fuel tank for less frequent fueling; easy-to-see windows for fuel and oil tank inspection**

A large-capacity tank reduces fueling frequency and enables extended non-stop operation. Easy-to-see inspection windows, mounted on both the fuel and oil tanks, permit reliable checking of oil and fuel levels as well as the degree of oil contamination.



For oil

- **Fuel Tank** (FD100, FD115) : **260L [68.7 USgal]**

(FD135, FD150E, 160E) : **280L [74.0 USgal]**

**Air cleaner with automatic dust ejector to prolong replacement cycle**

This air cleaner automatically exhausts air-borne dust to reduce clogging of the filter element, thus enhancing suction efficiency and prolonging the element's replacement cycle.

**Reserve tank for maintaining Engine coolant at a constant level (thus eliminating troublesome refilling)**




**High serviceability: non-bolted floor plates and side covers and quick-open/close engine hood**

## STRENGTH

**A high-rigidity frame for enhanced durability and load-handling performance**

Use of a mainframe structure comprising a single, thick steel plate provides high rigidity against twisting caused by static steering, turning, or unevenness of the road surface, thus achieving excellent vehicle durability and load-handling performance.



**Highly rigid mast construction to ensure reliability**

Use of an outer mast of rolled steel rails as well as parts of sufficient strength at every portion of the forklift ensures high strength and durability.



**Komatsu's original Hydraulic Suspension Cab (HSC) mount provides the ultimate in operator comfort even during extended operation**

Komatsu's original HSC mount system raises the operator's cab from the vehicle body with a hydraulic suspension that absorbs most travel vibration, thereby helping to reduce operator fatigue.



# Wide Variety of Attachment & Options to Meet All Your Work application & Environment Needs

## Options

Automatic Transmission
Wet disc brake
Operator Presence Sensing (OPS) system
UL specification
Cold climate specification (-30 degree)
Rotating light
Rear working light
Speedometer
Load indicator
Special length forks
Extension forks
Air cleaner with pre-cleaner
Spark arrester
Rear under mirror
Steel cabin
Air conditioner
Heater
Rotating seat
Fuel cap with key

## Steel Cabin



**Wide visibility even under severe working conditions for a comfortable and quiet working environment**

- Front and rear corners of glass for maximum visibility
- Quick-release door lock lever
- Cabin ceiling-mounted air conditioner for expanded operation space
- A high-mount cabin can be selected for an elevated view depending on the load
- Attachable wipers for front, rear and roof glasses (two wipers for the front glass, window washers for front and rear glasses)
- Built-in high-capacity alternator
- Room illumination

## Attachments

Side shifter
Side shift fork positioner (Independent move)
Fork positioner (Independent move)
Fork positioner with side shift function (Simultaneous move)
Manipulator*
Ram*
Crane*
Pole carrier fork*
Furnace charger*
Tyre handler*

\*Available upon request

## Tyre Handler




**Komatsu's exclusive design provide reliability and versatility.**

This attachment holds and rotates a huge construction machinery tyre, making the tyre exchange faster and smoother.

## Side shifter · Fork positioner






**Enhancing forward visibility for smooth fork positioning**





# CAPACITY CHART

**Maximum Load and Overall Height of Mast by Lifting Height (Double mast, load center: 600mm)**

Model	FD100-8				FD115-8				FD135-8			
	Maximum fork height mm (in)	Overall height mm (in) Lowered/Extended	Load capacity* kg (lb)	Free lift mm (in)	Back tilt restriction	Overall height mm (in) Lowered/Extended	Load capacity* kg (lb)	Free lift mm (in)	Back tilt restriction	Overall height mm (in) Lowered/Extended	Load capacity* kg (lb)	Free lift mm (in)
3000 (118)	2890/4400 (113.8/173.2)	10000 (22,000)	0 (0)	12°	3160/4670 (124.4/183.9)	11500 (25,000)	0 (0)	12°	3170/4680 (124.8/184.3)	13500 (30,000)	0 (0)	12°
3300 (130)	3040/4700 (119.7/185.0)	10000 (22,000)	3310/4970 (130.3/195.7)		11500 (25,000)	3320/4980 (130.7/196.1)			13500 (30,000)			
3500 (138)	3140/4900 (123.6/192.9)	10000 (22,000)	3410/5170 (134.3/203.5)		11500 (25,000)	3420/5180 (134.6/203.9)			13500 (30,000)			
3700 (146)	3240/5100 (127.6/200.8)	10000 (22,000)	3510/5370 (138.2/211.4)		11500 (25,000)	3520/5380 (138.6/211.8)			13500 (30,000)			
4000 (157)	3390/5400 (133.5/212.6)	10000 (22,000)	3760/5770 (148.0/219.3)		11500 (25,000)	3770/5780 (148.4/227.6)			13500 (30,000)			
4500 (177)	3740/6000 (147.2/236.2)	10000 (22,000)	4010/6270 (157.9/246.8)		11500 (25,000)	4020/6280 (158.3/247.2)			13500 (30,000)			
5000 (197)	4140/6650 (163.0/261.8)	10000 (22,000)	4460/6970 (175.6/274.4)		11500 (25,000)	4470/6980 (176.0/274.8)			13500 (30,000)			
5500 (217)	4440/7200 (174.8/283.5)	9000 (19,800)	4710/7470 (185.4/294.1)		10000 (22,000)	4720/7480 (185.8/294.5)			12000 (26,500)			
6000 (236)	4690/7700 (184.6/303.1)	8000 (17,600)	4960/7970 (195.3/313.8)		9000 (19,800)	4970/7980 (195.7/314.2)			11000 (24,300)			



Model	FD150E-8				FD160E-8			
	Maximum fork height mm (in)	Overall height mm (in) Lowered/Extended	Load capacity* kg (lb)	Free lift mm (in)	Back tilt restriction	Overall height mm (in) Lowered/Extended	Load capacity* kg (lb)	Free lift mm (in)
3000 (118)	3270/4780 (128.7/188.2)	15000 (33,000)	0 (0)	12°	3290/4800 (129.5/189.0)	16000 (35,300)	0 (0)	12°
3300 (130)	3420/5080 (134.6/200.0)	15000 (33,000)			3440/5100 (135.4/200.8)	16000 (35,300)		
3500 (138)	3520/5280 (138.6/207.9)	15000 (33,000)			3540/5300 (139.4/208.7)	16000 (35,300)		
3700 (146)	3620/5480 (142.5/215.7)	15000 (33,000)			3640/5500 (143.3/216.5)	16000 (35,300)		
4000 (157)	3770/5780 (148.4/227.6)	15000 (33,000)			3790/5800 (149.2/228.3)	16000 (35,300)		
4500 (177)	4020/6280 (158.3/247.2)	15000 (33,000)			4040/6300 (159.1/248.0)	16000 (35,300)		
5000 (197)	4470/6980 (176.0/274.8)	15000 (33,000)			4490/7000 (176.8/275.6)	16000 (35,300)		
5500 (217)	4720/7480 (185.3/294.5)	13500 (29,800)			4740/7500 (186.6/295.3)	14500 (32,000)		
6000 (236)	4970/7980 (195.7/314.2)	12000 (26,500)			4990/8000 (196.5/315.0)	13000 (28,700)		



Standard mast is shown in broad frame.  
\*Load capacity at 600mm (24in.) load center.

Capacities shown are for trucks equipped with 2-stage view mast up through 5000mm (197in.) maximum fork

Performance specifications are affected by the conditions of the vehicle and how it is equipped as well as the nature and conditions of the operating area. If these specifications are critical, please discuss the proposed application with your distributor or dealer.

## Specifications

Characteristics	1.2 Model		Manufacturer's Designations		FD100-8	FD115-8	FD135-8	FD150E-8	FD160E-8	1.2	
		1.3	Power Type	Electric, Diesel, Gasoline, LPG, Cable		Diesel	Diesel	Diesel	Diesel	Diesel	1.3
	1.4	Operation Type	Pedestrian, Drive Standing, Sitting, Order Picking		Sitting	Sitting	Sitting	Sitting	Sitting	1.4	
	1.5	Rated Capacity	Q	Rated Capacity	kg (lb)	10000 (22,000)	11500 (25,000)	13500 (30,000)	15000 (33,000)	16000 (35,000)	1.5
	1.6	Load Center	c	Rated Load Center	mm (in)	600 (24)	600 (24)	600 (24)	600 (24)	600 (24)	1.6
	1.8	Load Distance	x	Front Axle Center to Fork Face	mm (in)	695 (27.4)	715 (28.1)	740 (29.1)	750 (29.5)	750 (29.5)	1.8
	1.9	Wheelbase	y		mm (in)	2800 (110.2)	2800 (110.2)	3100 (122.0)	3100 (122.0)	3100 (122.0)	1.9
Weight	2.1	Service Weight			kg (lb)	12980 (28,620)	14360 (31,660)	15480 (34,130)	16570 (36,530)	17200 (37,920)	2.1
	2.2	Axle Loading	Loaded	Front	kg (lb)	20860 (45,990)	23490 (51,790)	26450 (58,310)	28740 (63,360)	30140 (66,450)	2.2
	2.2.1			Rear	kg (lb)	2120 (4,670)	2370 (5,220)	2530 (5,580)	2830 (6,240)	3060 (6,750)	2.2.1
	2.3		Unloaded	Front	kg (lb)	6230 (13,730)	6590 (14,530)	7110 (15,670)	7210 (15,900)	7170 (15,810)	2.3
2.3.2	Rear			kg (lb)	6750 (14,880)	7770 (17,130)	8370 (18,450)	9360 (20,640)	10030 (22,110)	2.3.2	
Tyres	3.1	Tyre Type				Pneumatic	Pneumatic	Pneumatic	Pneumatic	Pneumatic	3.1
	3.2	Tyre Size	Front			9.00-20-14PR (I)	10.00-20-14PR (I)	11.00-20-14PR (I)	11.00-20-16PR (I)	12.00-20-16PR (I)	3.2
	3.3			Rear	9.00-20-14PR (I)	10.00-20-14PR (I)	11.00-20-14PR (I)	11.00-20-16PR (I)	12.00-20-16PR (I)	3.3	
	3.5	Number of Wheel	Front/Rear (x=driven)			4x/2	4x/2	4x/2	4x/2	4x/2	3.5
	3.6	Tread, Front	b10		mm (in)	1700 (66.9)	1700 (66.9)	1770 (69.7)	1770 (69.7)	1770 (69.7)	3.6
	3.7	Tread, Rear	b11		mm (in)	1900 (74.8)	1890 (74.4)	1890 (74.4)	1890 (74.4)	1870 (73.6)	3.7
	Dimensions	4.1	Tilting Angle	$\alpha/\beta$	Forward/Backward	degree	6/12	6/12	6/12	6/12	6/12
4.2		Mast Height, Lowered	h1	with Std. Mast	mm (in)	2890 (113.8)	3160 (124.4)	3170 (124.8)	3270 (128.7)	3290 (129.5)	4.2
4.3		Std. Free Lift	h2	with Std. Mast from Ground	mm (in)	0 (0.0)	0 (0.0)	0 (0.0)	0 (0.0)	0 (0.0)	4.3
4.4		Std. Lift Height	h3	with Std. Mast from Ground	mm (in)	3000 (118)	3000 (118)	3000 (118)	3000 (118)	3000 (118)	4.4
4.5		Mast Height, Extended	h4	with Std. Mast	mm (in)	4400 (173.2)	4670 (183.9)	4680 (184.3)	4780 (188.2)	4800 (189.0)	4.5
4.7		Height, Overhead Guard	h6		mm (in)	2780 (109.4)	2800 (110.2)	2810 (110.6)	2810 (110.6)	2830 (111.4)	4.7
4.19		Length, with Std. Forks	l1		mm (in)	5465 (215.2)	5505 (216.7)	5860 (230.7)	5920 (233)	6020 (237)	4.19
4.20		Length, to fork face	l2		mm (in)	4245 (167.1)	4285 (168.7)	4640 (182.7)	4700 (185)	4800 (189)	4.20
4.21		Width, at tyre	b1		mm (in)	2280 (89.8)	2310 (90.9)	2410 (94.9)	2410 (94.9)	2480 (97.6)	4.21
4.22		Forks	s/e/l	Thickness/Width/Lengh	mm (in)	75x170x1220 (3.0x6.7x48.0)	75x185x1220 (3.0x7.3x48.0)	80x185x1220 (3.1x7.3x48.0)	85x190x1220 (3.3x7.5x48.0)	85x210x1220 (3.3x8.3x48.0)	4.22
4.23		Fork Carriage Class				Pin Mount	Pin Mount	Pin Mount	Pin Mount	Pin Mount	4.23
4.24		Width, Fork Carriage	b3		mm (in)	2140 (84.3)	2140 (84.3)	2210 (87.0)	2210 (87.0)	2210 (87.0)	4.24
4.31		Ground Clearance	m1	Under the Mast	mm (in)	250 (9.8)	250 (9.8)	260 (10.2)	250 (9.8)	270 (10.6)	4.31
4.32			m2	at the center of wheelbase	mm (in)	325 (12.8)	345 (13.6)	350 (13.8)	350 (13.8)	370 (14.6)	4.32
4.33		Right Angle Stacking Aisle*	Ast	plus load length	mm (in)	4695 (184.8)	4725 (186.0)	5090 (200.4)	5150 (202.8)	5250 (206.7)	4.33
4.35	Turning Radius	Wa		mm (in)	4000 (157.5)	4010 (157.9)	4350 (171.3)	4400 (173.2)	4500 (177.2)	4.35	
Performance	5.1	Travel Speed (FWD)	Loaded, 1st/2nd/3rd	km/h (mph)	8.5/18/28 (5.3/11.2/17.4)	8.5/19/28 (5.3/11.8/17.4)	9/19.5/27.5 (5.6/12.1/17.1)	9/19.5/27.5 (5.6/12.1/17.1)	9.5/20/28 (5.9/12.4/17.4)	5.1	
	5.1.1		Unloaded, 1st/2nd/3rd	km/h (mph)	9/20/32 (5.6/12.4/19.9)	9/21/32 (5.6/13.0/19.9)	9.5/21/32 (5.9/13.0/20.2)	9.5/21/32 (5.9/13.0/20.2)	10/21.5/32 (6.2/13.4/20.5)	5.1.1	
	5.2	Lifting Speed	Loaded/Unloaded	mm/s (fpm)	470/500 (93/98)	430/450 (85/89)	350/375 (69/74)	325/350 (64/69)	320/345 (63/68)	5.2	
	5.3	Lowering Speed	Loaded/Unloaded	mm/s (fpm)	400/500 (78.7/98.4)	400/500 (78.7/98.4)	400/500 (78.7/98.4)	400/400 (79/79)	400/400 (79/79)	5.3	
	5.6	Max. Drawbar Pull	Loaded	kN (lb)	89 (20,010)	87 (19,610)	85 (19,150)	80 (18,160)	80 (18,030)	5.6	
	5.8	Max. Gradeability	Loaded 1.5km/h, 3min rating	%	40	34	28	25	23	5.8	
	5.10	Service Brake	Operation/Control		Foot/Hydraulic, Powered	Foot/Hydraulic, Powered	Foot/Hydraulic, Powered	Foot/Hydraulic, Powered	Foot/Hydraulic, Powered	5.10	
	5.11	Parking Brake	Operation/Control		Hand/Mechanical	Hand/Mechanical	Hand/Mechanical	Hand/Mechanical	Hand/Mechanical	5.11	
5.12	Steering	Type		Hydraulic Power Steering	Hydraulic Power Steering	Hydraulic Power Steering	Hydraulic Power Steering	Hydraulic Power Steering	5.12		
6.4	Battery	Voltage/Capacity at 5-hour rating	V/Ah		24/80	24/80	24/80	24/80	24/80	6.4	
Drive	7.1	Maker/Model			Komatsu SAA6D107E-1	Komatsu SAA6D107E-1	Komatsu SAA6D107E-1	Komatsu SAA6D107E-1	Komatsu SAA6D107E-1	7.1	
	7.2	Rated Output, SAE net		kW (HP)	122 (164)	122 (164)	122 (164)	122 (164)	122 (164)	7.2	
	7.3	Rated Speed		min <sup>-1</sup>	2200	2200	2200	2200	2200	7.3	
	7.3.1	Max Torque, SAE net		N-m (lbf·ft)@min <sup>-1</sup>	575 (424)@1600	575 (424)@1600	575 (424)@1600	575 (424)@1600	575 (424)@1600	7.3.1	
7.4	No. of Cylinder/Displacement		cm <sup>3</sup> (cu.in)	6/6690 (408)	6/6690 (408)	6/6690 (408)	6/6690 (408)	6/6690 (408)	7.4		
Others	7.6	Fuel Tank Capacity		Ltr (US gal)	260 (68.7)	260 (68.7)	280 (74.0)	280 (74.0)	280 (74.0)	7.6	
	8.2	Relief Pressure for Attachment		bar (psi)	216 (3,150)	216 (3,150)	216 (3,150)	216 (3,150)	216 (3,150)	8.2	
	8.2.1	Hydraulic Tank Capacity		Ltr (US gal)	180 (48)	180 (48)	210 (55)	210 (55)	210 (55)	8.2.1	
	8.6	Clutch			Torque Converter	Torque Converter	Torque Converter	Torque Converter	Torque Converter	8.6	

\*Right Angle Stacking Aisle does not include any operational clearance.  
Specifications are subject to change without notice.  
The performance values indicated herein represent nominal values obtained under typical operating conditions.

## Standard Equipment

Headlights  
Turn signal lamps  
Charge warning lamps  
Safety checker  
Hourmeter  
Fuel gauge  
Torque converter oil temperature gauge  
Water temperature gauge  
Neutral safety swich  
Brake oil pressure warning buzzer  
Torque converter oil cooler  
Tiltable steering column  
Hydraulic power brake  
Horn  
Overhead guard  
Drawbar pin  
Cyclonic air cleaner  
Notch-release parking brake  
Back-up buzzer  
Rear view mirror



Full-open steps



Notch-release parking brake



Head guard with front/rear gutters

## Dimensional Drawing

